

X Series Lithium Battery

51.2V 200AH 10.24KWH

· Safety and Intelligent

Long life LiFePO4 cells, high energy density, build in BMS and passive protection

· Easy to Install and Use

Modular design, simple operation

· Long Life Span

10 years design life, more than 6000cycles

Adaptable to Harsh Environment

Adapt to wide range of temperature and humidity

Support Bluetooth/WIFI function

optional) Can be controlled remotely to reduce operation and naintenance costs

Multi-scenario application

ousehold use, small industrial and commercial applications





Lithium Battery

Technical Parameters

Nominal voltage	51.2V
Nominal capacity	200Ah
Energy	10.24kwh
Interal Resistance	≤200mΩ
Cycle Life	>6000 cycles @ 0.2C 80%D.O.D
Months Self Discharge	<3%
Efficiency of Charge	99.5%@ 0.20
Effciency of Discharge	96-99%@ 1C
Charge Voltage	58.4±0.5V
Charge Mode	cc/cv
Charger Current	40A
Max Charge Current	200A
Charge Cut-off Voltage	58.4
Continuous discharge Current	40A
max discharge Current	200A
Discharge Cut-off Voltage	43.2V
Charge Temperature	0℃ to 45℃
Discharge Temperature	-20℃ to 55 ℃
Storage Temperature	-10 ℃ to 40 ℃
Water Dust Resistance	IP20
Cell & Method	3.2V100Ah-16S2F
Terminal	200A
Protocol (optional)	RS232/RS485/CAN/BLUETOOTH/WIFI
BMS	200A
Safety & Certification	CELL:UL1642/UL1973/IEC62619/CE/CB/UN38.3/UL9540/ROHS/REACH
Size (mm)	812*513*205(D*W*H)
Net weight (kg)	88KG
Wooden box package size (mm)	940*555*405
Quantity of loading	120pcs/20ft 240pcs/40ft

Notes

- *1 Test conditions: Based on the factory date, charge and discharge rate at 0.2C at 100% discharge depth (DoD) and 25 $\,^\circ$
- * 2 The weight of the battery module is based on the actual product, with a tolerance of \pm 3% allowed
- *3 The installation of battery packs is related to product quality assurance, safe and stable operation. Please follow the requirements of the user manual for standardized installation, use, and routine maintenance

Compatibility Inverters

















^{*}Only a part of inverter brands are shown, please contact us for more information.

